



More than colour

CHROMATIC WOOD PRIMER

PRODUCT DESCRIPTION AND USES:

A white, solvent-based primer Designed specifically for use on interior and exterior new and unpainted hard and soft wood before applying a paint topcoat. It ensures better adhesion of paint to the surface, increases paint durability and provides additional protection to the surface being painted. It is slow drying therefore, provides excellent penetration and sealing properties on wood and provides a good bond for subsequent coats of paint.

A white oil-based primer for interior and exterior wood, made to provide proper adhesion to wood for subsequent coats. Has good penetrating properties. Provides a strong bond between the undercoat and timber surface.

SURFACE PREPARATION:

New Dry Wood Work: Sand down wood to desired smoothness, dust of all loose materials before applying wood primer. The first coat thinned more than subsequent coats to allow better penetration, sealing and adhesion
Previously Painted Wood Work: Prepare the surface and patch prime all bare timber with 1 coat Chromatic Wood Primer.

THINING:

chromatic White Spirit. Avoid over thinning. Stir well before use.

EQUIPMENT CLEANING:

Chromatic White Spirit.

DRYING TIME:

Surface Dry: 4hours. Thorough Dry: 8hours. Re-coatable: 16hours.

COLOUR RANGE:

White or Pink

SPREADING CAPACITY:

13-15m²/l on smooth, non-porous surfaces. The spreading capacity will vary considerably depending on the texture and porosity of the timber.

PACK SIZES:

1 Litre, 4 Liters, 20 Liters

DISCLAIMER

The recommendations contained herein are given in good faith and meant to guide the user in accordance with good painting practices. They are gained from our tests and experiences and are believed to be accurate and reliable.

No warranty/guarantee is implied by the recommendations contained herein since the conditions of use; application method, substrate and cleanliness of the substrate are beyond the control of Chromatic Paints Uganda.

Technology may change with time, necessitating changes to this Technical Data Sheet (TDS). Chromatic Paints Uganda reserves the right to amend the TDS without any further notice. It is the responsibility of the user to ensure that the latest TDS is being used for reference

For health & safety information, please refer to our Material Safety Data Sheet (MSDS)

