



More than colour

## CHROMATIC STAIN BLOCK SEALER

**PRODUCT DESCRIPTION AND USES:**

Chromatic Stain Block sealer provides a protective basecoat to ensure smooth and even paint application on problem walls inside the home. It's formulated with a synthetic binder which dries rapidly, this high-performance sealer/primer covers and seals stubborn stains including water stains, nicotine and smoke stains, crayon and pen, preventing them from bleeding through your topcoat of paint.

**SURFACE PREPARATION:**

**New Surfaces:** All surfaces must be sound, clean, suitably dry and free from anything that will interfere with the adhesion of the materials to be applied. When used on timber degrease with methylated spirits. Prior to priming the moisture content should not exceed 18%.

**Previously Decorated Surfaces:** All surfaces must be sound, clean, suitably dry and free from anything that will interfere with the adhesion of the materials to be applied e.g. dirt, grease etc. Remove all loose, suspect and failing paint. Remove all dust.

**APPLICATION:**

Stir well before and during use. Apply using good quality tools - synthetic brush or medium pile roller. For airless spray dilution with enamel thinner may be required. Stir well before use. On uncoated, porous wall and ceiling surfaces the first coat can be thinned with up to 10%. Stubborn stains may require an additional coat.

**SPREADING CAPACITY:**

Up to 12m<sup>2</sup> per litre on smooth surfaces

**FINISH:**

Matt

**THINNER & EQUIPMENT CLEANER:**

Thin with Chromatic Enamel thinner

**PACK SIZES:**

1L, 4L

**DRYING TIME:**

Touch dry in 2 hours, Hard dry 12hrs. Allow a minimum of 15 hours before recoating. Allow for adequate ventilation during the drying period.

**COLOUR RANGE:**

White

## DISCLAIMER

The recommendations contained herein are given in good faith and meant to guide the user in accordance with good painting practices. They are gained from our tests and experiences and are believed to be accurate and reliable.

No warranty/guarantee is implied by the recommendations contained herein since the conditions of use; application method, substrate and cleanliness of the substrate are beyond the control of Chromatic Paints Uganda.

Technology may change with time, necessitating changes to this Technical Data Sheet (TDS). Chromatic Paints Uganda reserves the right to amend the TDS without any further notice. It is the responsibility of the user to ensure that the latest TDS is being used for reference

For health & safety information, please refer to our Material Safety Data Sheet (MSDS)

